



OptiSpace

BCB500 LED25-4S/830 A DF DGR

OPTISPACE BOLLARD, LED Module 2500 lm, 830 warm white, Power supply unit with DALI interface, Safety class I, Asymmetrical, Black

OptiSpace is a creative bollard solution which enables you to build a more attractive, citizen-centric inner-city space by avoiding verticalization of the urban landscape. OptiSpace delivers all this and more while delivering an attractive TCO for your investment. Enabled by the different control options you can reduce energy consumption and minimize TCO further and thanks to the excellent and optimized light distribution options you can maximize spacing between the bollards, thereby minimizing the number of light points needed to be installed. To support different design schemes, OptiSpace is also available in different colors: Philips Ultra Dark Grey is the standard color and other colors are available on request.

Product data

General Information	
Lamp family code	LED25 [LED Module 2500 lm]
Light source replaceable	Yes
Number of gear units	1 unit
Driver included	Yes
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Light source engine type	LED
Product family code	BCB500 [OPTISPACE BOLLARD]
Lighting Technology	LED
Value ladder	Specification
CE mark	Yes

Warranty period	5 years
Flammability mark	For mounting on normally flammable surfaces
ENEC mark	ENEC mark
EU RoHS compliant	Yes
Light Technical	
Upward light output ratio	0
Luminous Flux	2,150 lm
Standard tilt angle posttop	-
Standard tilt angle side entry	0°
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	140 lm/W

Color rendering index (CRI)	>80
Light source color	830 warm white
Optical cover type	Polycarbonate bowl/cover clear
Luminaire light beam spread	21° - 26° x 200°
Optic type outdoor	Asymmetrical

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	15 A
Inrush time	0.36 ms
Power Consumption	21.9 W
Power Factor (Fraction)	0.97
Connection	-
Cable	Cable 1.5 m without plug
Number of products on MCB of 16 A type B 23	

Temperature

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit with DALI interface
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Aluminum
Optic material	Polymethyl methacrylate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	Black
Mounting device	Baseplate
Optical cover shape	Cylinder/cylindrical
Optical cover finish	Clear

Overall length	270 mm
Overall width	270 mm
Overall height	848 mm
Effective projected area	0.172 m²
Dimensions (Height x Width x Depth)	848 x 270 x 270 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 6 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0,3818; 0,3796) SDCM<3
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)


Driver failure rate at 5000 h	0.5 %
-------------------------------	-------

Product Data

Order product name	BCB500 LED25-4S/830 A DF DGR
Full product name	BCB500 LED25-4S/830 A DF DGR
Full product code	871869948117900
Order code	912300024099
Material Nr. (12NC)	912300024099
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699481179
Numerator - Packs per outer box	1
EAN/UPC - Case	8718699481179

Dimensional drawing

Dimensional drawing



Dimensional drawing

