



WAML1D/WBML1D Mini Floodlight LED

WAML,LED,3.8W,12V,3000K

Floodlight, Mini Arch w/ Frosted Shroud, Bronze, 3.8W LED, 3000K, 12V

The WAML1D/WBML1D is an LED flood light family for general landscape and sign illumination, offered in low and line voltage in a variety of sources. The optical assembly is a clear or frosted tempered glass lens and features a cool white (4,000K) or warm white (3,000K) LED source.

Product data

General Information	
Lamp Source Code	LED
Lamp Watts	3.8
Number of Lamps	1
Color Temperature	3000K
CRI	80
Photometric Distribution Type	General Diffuse
Mounting	NPT/NPS
Operating and Electrical	
Voltages	12 V
Luminaire Input Watts	3.8
Initial Performance (IEC Compliant)	
Luminaire Lumens	897

Product Data	
Order product name	WAML,LED,3.8W,12V,3000K
EAN/UPC - Product	190096019823
Order code	WAML1DW3F-HS7
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912400129334
Net Weight (Piece)	0.001 kg
Commercial Code	WAML1DW3F-HS7
Catalog Number Description	Floodlight, Mini Arch w/ Frosted Shroud, Bronze, 3.8W LED, 3000K, 12V
Quick Ship	Spec Smart (10 Days) USA