



# Vaya Linear MP

## BCP425 50 3000 L1210 CE

Vaya Linear MP is a reliable and cost-effective LED lighting fixture designed for fixed or dynamic colorful lighting effects. Offering a choice of wide or elliptical beams, Vaya Linear MP is ideal for wall washing and grazing applications. Integrated power and unified power and data connectors make installation fast, easy and reliable.

#### **Product data**

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Beam angle of light source	50 °
Light source color	Neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GC [ Clear glass]
CE mark	CE mark
UL mark	-
CQC mark	-
Lifetime to 70% luminous flux	60000 h
PSE mark	PSE mark
Operating and Electrical	
Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Glass

Optical cover/lens material	Tempered glass	
Optical cover/lens shape	Flat	
Optical cover/lens finish	Clear	
Length	1210 mm	
Approval and Application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK06 [ 1 J]	
Initial Performance (IEC Compliant)		
Initial luminous flux (system flux)	3392 lm	
Initial LED luminaire efficacy	57.9 lm/W	
Init. Corr. Color Temperature	3000 K	
Init. Color Rendering Index	78	
Initial input power	60 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 70% at 25°C Calculated	100000	
Lumen Maintenance 70% at 25°C Reported	60000	
Lumen Maintenance 70% at 40°C Calculated	100000	
Lumen Maintenance 70% at 40°C Reported	60000	
Lumen Maintenance 80% at 25°C Reported	60000	
Lumen Maintenance 80% at 40°C Calculated	100000	

Datasheet, 2018, December 3 data subject to change


## Vaya Linear MP

Lumen Maintenance 80% at 40°C Reported	60000
Lumen Maintenance 80% at 50°C Calculated	100000
Lumen Maintenance 90% at 25°C Calculated	62000
Lumen Maintenance 90% at 25°C Reported	60000
Lumen Maintenance 90% at 40°C Calculated	62000
Lumen Maintenance 90% at 40°C Reported	60000
Application Conditions	
Ambient temperature range	-40 to +104 °F
Product Data	
Order product name	BCP425 50 3000 L1210 CE

EAN/UPC - Product	8718291625698
Order code	912400130119
Local order code	
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	912400130119
Net Weight (Piece)	3.760 kg



### **Dimensional drawing**



Vaya

