

# Vaya Linear MP

## BCP425 50 5000 L1210 CE

Vaya Linear MP is a reliable and cost-effective LED lighting fixture designed for fixed or dynamic colourful lighting effects. Offering a choice of wide or elliptical beams, Vaya Linear MP is ideal for wall washing and grazing applications. Integrated power and unified power and data connectors make installation fast, easy and reliable.

### Product data

| General Information | |
|---|---|
| **Lamp family code** | LED-HB [ LED High Brightness] |
| **Beam angle of light source** | 50 ° |
| **Light source colour** | Cool white |
| **Light source replaceable** | No |
| **Driver included** | Yes |
| **Optical cover/lens type** | GC [ Clear glass] |
| **CE mark** | CE mark |
| **UL mark** | No |
| **CQC mark** | - |
| **Lifetime to 70% luminous flux** | 60000 h |
| **PSE mark** | PSE mark |

| Operating and Electrical | |
|---|---|
| **Input voltage** | 100 to 277 V |
| **Input frequency** | 50 to 60 Hz |

| Controls and Dimming | |
|---|---|
| **Dimmable** | Yes |

| Mechanical and Housing | |
|---|---|
| **Housing material** | Extruded aluminium |
| **Optic material** | Glass |
| **Optical cover/lens material** | Tempered glass |
| **Optical cover/lens shape** | Flat |
| **Optical cover/lens finish** | Clear |
| **Length** | 1210 mm |
| **Colour** | Dark Grey |

| Approval and Application | |
|---|---|
| **Ingress protection code** | IP66 [ Dust penetration-protected, jet-proof] |
| **Mech. impact protection code** | IK06 [ 1 J] |

| Initial Performance (IEC Compliant) | |
|---|---|
| **Initial luminous flux** | 3360 lm |
| **Init. Corr. colour temperature** | 5000 K |
| **Initial input power** | 60 W |

| Over Time Performance (IEC Compliant) | |
|---|---|
| **Lumen Maintenance 70% at 25°C Calculated** | 100000 |
| **Lumen Maintenance 70% at 25°C Reported** | 60000 |
| **Lumen Maintenance 70% at 40°C Calculated** | 100000 |
| **Lumen Maintenance 70% at 40°C Reported** | 60000 |

# Vaya Linear MP

| | |
|---|---|
| **Lumen Maintenance 80% at 25°C Reported** | 60000 |
| **Lumen Maintenance 80% at 40°C Calculated** | 100000 |
| **Lumen Maintenance 80% at 40°C Reported** | 60000 |
| **Lumen Maintenance 80% at 50°C Calculated** | 100000 |
| **Lumen Maintenance 90% at 25°C Calculated** | 62000 |
| **Lumen Maintenance 90% at 25°C Reported** | 60000 |
| **Lumen Maintenance 90% at 40°C Calculated** | 62000 |
| **Lumen Maintenance 90% at 40°C Reported** | 60000 |

## Application Conditions


| | |
|---|---|
| **Ambient temperature range** | -40 to +40 °C |

## Product Data


| | |
|---|---|
| **Full product code** | 871829162605399 |
| **Order product name** | BCP425 50 5000 L1210 CE |
| **EAN/UPC – product** | 8718291626053 |
| **Order code** | 62605399 |
| **Numerator – quantity per pack** | 1 |
| **Numerator – packs per outer box** | 4 |
| **Material no. (12NC)** | 912400130155 |
| **Net weight (piece)** | 3.760 kg |

IK06

## Dimensional drawing




Vaya




Vaya

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.