



ColorBurst Powercore gen2

BCP462 G2 19xLED-HB/RGB BZ CQC

19 pcs - Red, green and blue - Bronze

ColorBurst Powercore gen2 is a high-output, exterior-rated LED lighting fixture designed for accent and site lighting. Architectural and landscape fixtures deliver full-color light output of up to 963 lumens to support a range of dynamic uplighting, floodlighting, and decorative lighting applications.

Product data

General Information	
Number of light sources	19 pcs
Beam angle of light source	8 °
Light source color	Red, green and blue
Light source replaceable	No
Driver included	Yes
Protection class IEC	Safety class I
Glare shielding accessories	Glare shield
Operating and Electrical	
Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz
Mechanical and Housing	
Color	Bronze
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]



Mech. impact protection code	IK10 [20 J vandal-resistant]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	927 lm
Initial LED luminaire efficacy	31 lm/W
Initial input power	30 W
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871829139362799
Order product name	BCP462 G2 19xLED-HB/RGB BZ CQC
EAN/UPC - Product	8718291393627
Order code	912400133320
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	912400133320

ColorBurst Powercore gen2

Net Weight (Piece) 5.510 kg

IP66 IK10

Dimensional drawing



ColorBurst Powercore gen2

ColorBurst Powercore gen2

