eW Burst Powercore gen2

eW Burst Powercore gen2, 2700 K, 6° Native (no spread lens), Bronze housing, Architectural

eW Burst Powercore gen2, 2700 K, 6° Native (no spread lens), Bronze housing, Architectural

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting.;Architectural and Landscape versions deliver high-quality white light output in a warm 2,700 K and a neutral 4,000 K to support a range of uplighting, floodlighting and decorative lighting applications.

Product data

General information	
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Luminaire light beam spread	6°
CE mark	CE mark
UL mark	UL and cUL mark

Operating and electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Colour	Bronze

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Vibration standard	Complies with ANSI C136.31, 3G
FCC mark	FCC Class A
Vibration rating	Complies with ANSI C136.31, 3G

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	1851 lm
Initial LED luminaire efficacy	64.7 lm/W
Init. Corr. Colour Temperature	2700 K
Init. Colour rendering index	81

eW Burst Powercore gen2

Initial input power	30 W

Over time performance (IEC compliant)

Lumen Maintenance 50% at 25 °C Calculated	100000
Lumen Maintenance 50% at 25 °C Reported	51000
Lumen Maintenance 50% at 50 °C Calculated	100000
Lumen Maintenance 50% at 50 °C Reported	51000
Lumen Maintenance 70% at 25 °C Calculated	84000
Lumen Maintenance 70% at 25 °C Reported	51000
Lumen Maintenance 70% at 50 °C Calculated	83000
Lumen Maintenance 70% at 50 °C Reported	51000
Lumen Maintenance 90% at 25 °C Calculated	28000
Lumen Maintenance 90% at 25 °C Reported	28000
Lumen Maintenance 90% at 50 °C Calculated	27000
Lumen Maintenance 90% at 50 °C Reported	27000

Application conditions


Ambient temperature range	-40 to +50 °C

Product data

Full product code	871869921566899
Order product name	BCP463 G2 19xLED-HB/2700 BZ
EAN/UPC – product	8718699215668
Order code	523-000098-10
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	912400133367
Net Weight (Piece)	5.510 kg
Commercial Code	523-000098-10
Catalogue number description	eW Burst Powercore gen2, 2700 K, 6° Native (no spread lens), Bronze housing, Architectural

IP66

Dimensional drawing



BCP463 G2 19xLED-HB/2700 BZ

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.