**PHILIPS** Lighting



# eW Burst Powercore gen2

# eW Burst Powercore gen2, 4000 K, 6° Native (no spread lens), White housing, Architectural

eW Burst Powercore gen2, 4000 K, 6° Native (no spread lens), White housing, Architectural

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in 2700 K, 3000 K, 3500 K, and 4000 K to support a range of uplighting, floodlighting, and decorative lighting applications.

## **Product data**

General information		Corrosion Resistance	Complies with ASTM B117 standard for >
Luminaire light beam spread	6°	_	1,500 hours
CE mark	CE mark	FCC mark	FCC Class A
UL mark	UL and cUL mark	Vibration Rating	Complies with ANSI C136.31, 3G
Operating and electrical		Initial performance (IEC complian	ıt)
Input Voltage	100 to 277 V	Initial luminous flux (system flux)	2096 lm
Input Frequency	50 to 60 Hz	Initial LED luminaire efficacy	74.6 lm/W
		Init. Corr. Color Temperature	4000 K
Mechanical and housing		Init. Color Rendering Index	81
Color	White	Initial input power	30 W
Approval and application		Over time performance (IEC compliant)	
Ingress protection code	IP60 [ Dust penetration-protected]	Lumen Maintenance 50% at 25°C Calculated 100000	
Vibration Standard	Complies with ANSI C136.31, 3G	Lumen Maintenance 50% at 25°C Repo	rted 51000

# eW Burst Powercore gen2

Lumen Maintenance 50% at 50°C Calculated	100000
Lumen Maintenance 50% at 50°C Reported	51000
Lumen Maintenance 70% at 25°C Calculated	84000
Lumen Maintenance 70% at 25°C Reported	51000
Lumen Maintenance 70% at 50°C Calculated	83000
Lumen Maintenance 70% at 50°C Reported	51000
Lumen Maintenance 90% at 25°C Calculated	28000
Lumen Maintenance 90% at 25°C Reported	28000
Lumen Maintenance 90% at 50°C Calculated	27000
Lumen Maintenance 90% at 50°C Reported	27000

-40 to +50 °C

871869921572999

Order product name	BCP463 G2 19xLED-HB/4000 WH	
EAN/UPC - Product	8718699215729	
Order code	523-000098-19	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	2	
Material Nr. (12NC)	912400133376	
Net Weight (Piece)	5.510 kg	
Catalog Number	523-000098-19	
Catalog Number Description	eW Burst Powercore gen2, 4000 K, 6°	
	Native (no spread lens), White housing,	
	Architectural	


## Application conditions

Ambient temperature range

#### Product data

Full product code

### Dimensional drawing



BCP463 G2 19xLED-HB/4000 WH



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2022, October 11 - data subject to change