



eColor Burst Powercore gen2

eColor Burst Powercore gen2, Green, 6° Native (no spread lens), Black Housing, Architectural

eColor Burst Powercore gen2, Green, 6° Native (no spread lens), Black Housing, Architectural

The eColor Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in red, green, blue and amber to support a range of uplighting, floodlighting and decorative lighting applications.

Product data

General Information		Colour	
Light source colour	Green	Black	
Light source replaceable	No	Approval and Application	
Optical cover/lens type	GT [Tempered glass]	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Luminaire light beam spread	6°	Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I (I)	Vibration standard	Complies with ANSI C136.31, 3G
CE mark	CE mark	Vibration rating	Complies with ANSI C136.31, 3G
UL mark	UL and cUL mark	Initial Performance (IEC Compliant)	
Operating and Electrical		Initial input power	30 W
Input Voltage	100 to 277 V	Application Conditions	
Input frequency	50 to 60 Hz	Ambient temperature range	-40 to +50 °C
Mechanical and Housing			
Length	210 mm		


eColor Burst Powercore gen2

Product Data	
Full product code	871869921634499
Order product name	BCP467 G2 19xLED-HB/GN BK
EAN/UPC – product	8718699216344
Order code	223-000086-16
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	912400133397

SAP net weight (piece)	5.510 kg
Commercial Code	223-000086-16
Catalogue number description	eColor Burst Powercore gen2, Green, 6° Native (no spread lens), Black Housing, Architectural



Dimensional drawing



eColor Burst Powercore gen2

