eColor Burst Powercore gen2

eColor Burst Powercore gen2, Amber, 6° Native (no spread lens), Black Housing, Architectural

eColor Burst Powercore gen2, Amber, 6° Native (no spread lens), Black Housing, Architectural

The eColor Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in red, green, blue and amber to support a range of uplighting, floodlighting and decorative lighting applications.

Product data

General Information

Light source colour	Amber
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Luminaire light beam spread	6°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark

Operating and Electrical

Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Housing configuration	BV [Basic version]
Length	210 mm
Colour	Black

Approval and Application

|	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G

eColor Burst Powercore gen2

Initial Performance (IEC Compliant)	
Initial input power	30 W

Application Conditions	
Ambient temperature range	–40 to +50 °C

Product Data	
Full product code	871869921650499
Order product name	BCP467 G2 19xLED-HB/AM BK
EAN/UPC – product	8718699216504
Order code	223-000086-40

SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	912400133422
SAP net weight (piece)	5.510 kg
Commercial Code	223-000086-40
Catalogue number description	eColor Burst Powercore gen2, Amber, 6° Native (no spread lens), Black Housing, Architectural

IK 08

Dimensional drawing

eColor Burst Powercore gen2

www.lighting.philips.com

2021, May 13 – data subject to change