Uni DMX controls and accessories

SSLCTR ACTIVESITE GATEWAY

Uni DMX controls and accessories, CE mark

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar). DMX Controls include main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device. Main Controller: Industrial computer that can control up to 6000 DMX universes. Stand-alone Controller: Fits for medium applications with up to 700 DMX universes. Wiring accessories include leader and jumper cables with male and female IP67 connectors and end-caps. Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes. DMX Amplifier: Compact, IP65 and low power repeater that can amplify the DMX signal for up 100 meters.

Product data

General Information	
CE mark	CE mark

Operating and Electrical	
Power Consumption	40 W

Mechanical and Housing	
Housing Color	Black

Product Data	
Order product name	SSLCTR ACTIVESITE GATEWAY

Full product name	SSLCTR ACTIVESITE GATEWAY
Full product code	871829164576400
Order code	64576400
Material Nr. (12NC)	912400133649
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291645764
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291645764