



Vaya Flood LP G2, White

Vaya Flood LP G2, 3000 K, 40°, CE/CQC/PSE

Vaya Flood LP G2, 3000 K, 40°, CE/CQC/PSE

Vaya Flood MP (gen2) is a reliable and cost effective LED flood lighting solution for both exterior use that minimizes the initial investment, while providing exceptional flexibility to create eye-catching flood, wash and accent lighting effects. A wide choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.

Product data

General information		Operating and electrical	
Lamp family code	LED-HB [LED High Brightness]	Input Voltage	100 to 240 V
Light source color	Neutral white	Input Frequency	50 to 60 Hz
Light source replaceable	No	Controls and dimming	
Driver included	Yes	Dimmable	Yes
Optical cover/lens type	Tempered glass	Mechanical and housing	
Luminaire light beam spread	40°	Housing Material	Aluminum die cast
Protection class IEC	Safety class I	Optic material	Glass
CE mark	CE mark	Optical cover/lens material	Tempered glass
CQC mark	CQC-mark	Optical cover/lens shape	Flat
Optic type outdoor	Medium beam angle 40°	Optical cover/lens finish	Clear
PSE mark	PSE mark	Color	Dark gray
Angle	40°		

Vaya Flood LP G2, White

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Vibration Standard	Complies with ANSI C136.31
Vibration Rating	Complies with ANSI C136.31

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	3123 lm
Initial LED luminaire efficacy	73 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	82
Initial input power	44 W

Over time performance (IEC compliant)	
Lumen Maintenance 70% at 25°C Calculated	71000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	71000
Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	45000
Lumen Maintenance 80% at 25°C Reported	45000
Lumen Maintenance 80% at 40°C Calculated	45000
Lumen Maintenance 80% at 40°C Reported	45000


Lumen Maintenance 90% at 25°C Calculated	23000
Lumen Maintenance 90% at 25°C Reported	23000
Lumen Maintenance 90% at 40°C Calculated	23000
Lumen Maintenance 90% at 40°C Reported	23000

Application conditions	
Ambient temperature range	-40 to +40 °C

Product data	
Full product code	871829164738699
Order product name	BCP432 3000 100-240 40 CQC PSE
EAN/UPC - Product	8718291647386
Order code	350-000015-02
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	912400133957
Net Weight (Piece)	2.770 kg
Catalog Number	350-000015-02
Catalog Number Description	Vaya Flood LP G2, 3000 K, 40°, CE/CQC/PSE



Dimensional drawing



BCP432 3000 100-240 40 CQC PSE

