



Vaya Flood LP Small

BCP432 5000 100-240 40 CE CQC PSE

Medium beam angle 40°

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures. Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colorful lighting effects that can bring a property to life. The robust Vaya Flood offers a wide choice of mono colors with a simple on-off switch and changing colors with a standard DMX512 controller. It is also extremely easy to install and aim.

Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [LED High Brightness]	Dimmable	Yes
Light source colour	Cool white	Mechanical and Housing	
Light source replaceable	No	Housing material	Aluminum die-cast
Driver included	Yes	Optic material	Glass
Optical cover/lens type	GT [Tempered glass]	Optical cover/lens material	Tempered glass
Luminaire light beam spread	40°	Optical cover/lens shape	Flat
Protection class IEC	Safety class I (I)	Optical cover/lens finish	Clear
CE mark	CE mark	Colour	Dark gray
CQC mark	CQC-mark	Approval and Application	
Outdoor optic type	Medium beam angle 40°	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
PSE mark	PSE mark	Mech. impact protection code	IK06 [1 J]
Angle	40°		
Operating and Electrical			
Input voltage	100 to 240 V		
Input frequency	50 to 60 Hz		

Vaya Flood LP Small

Initial Performance (IEC Compliant)

Init. Corr. colour temperature 5000 K

Over Time Performance (IEC Compliant)

Lumen Maintenance 70% at 25°C Calculated 71000

Lumen Maintenance 70% at 25°C Reported 60000

Lumen Maintenance 70% at 40°C Calculated 71000

Lumen Maintenance 70% at 40°C Reported 60000

Lumen Maintenance 80% at 25°C Calculated 45000

Lumen Maintenance 80% at 25°C Reported 45000

Lumen Maintenance 80% at 40°C Calculated 45000

Lumen Maintenance 80% at 40°C Reported 45000

Lumen Maintenance 90% at 25°C Calculated 23000

Lumen Maintenance 90% at 25°C Reported 23000

Lumen Maintenance 90% at 40°C Calculated 23000

Lumen Maintenance 90% at 40°C Reported 23000

Application Conditions

Ambient temperature range -40 to +40 °C

Product Data

Full product code 871829164753999

Order product name BCP432 5000 100-240 40 CE CQC PSE

EAN/UPC – product 8718291647539

Order code 64753999

Numerator – quantity per pack 1


Numerator – packs per outer box 4

Material no. (12NC) 912400133967

Net weight (piece) 2.770 kg



Dimensional drawing



Vaya

