



Vaya Flood LP Small

BCP431 RGB 100-240 20 UL

Medium beam angle 20°

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures. Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colorful lighting effects that can bring a property to life. The robust Vaya Flood offers a wide choice of mono colors with a simple on-off switch and changing colors with a standard DMX512 controller. It is also extremely easy to install and aim.

Product data

| General Information | |
|--------------------------|-------------------------------|
| Lamp family code | LED-HB [LED High Brightness] |
| Light source color | Red, green and blue (RGB) |
| Light source replaceable | No |
| Driver included | Yes |
| Optical cover/lens type | GT [Tempered glass] |
| Protection class IEC | Safety class I (I) |
| UL mark | UL and cUL mark |
| Optic type outdoor | Medium beam angle 20° |
| PSE mark | No |
| Angle | 20° |
| Operating and Electrical | |
| Input Voltage | 100 to 240 V |
| Input Frequency | 50 to 60 Hz |

| Controls and Dimming | | |
|-------------------------------------|---|--|
| Dimmable | Yes | |
| Mechanical and Housing | | |
| Housing Material | Aluminum die-cast | |
| Optic material | Glass | |
| Optical cover/lens material | Tempered glass | |
| Optical cover/lens shape | Flat | |
| Optical cover/lens finish | Clear | |
| Approval and Application | | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] | |
| Mech. impact protection code | IK06 [1 J] | |
| Initial Performance (IEC Compliant) | | |
| Initial luminous flux (system flux) | 1344 lm | |
| Initial LED luminaire efficacy | 33.6 lm/W | |

Datasheet, 2018, September 4 data subject to change

Vaya Flood LP Small

| Lumen Maintenance 50% at 25°C Calculated 100000 Lumen Maintenance 50% at 25°C Reported 60000 Lumen Maintenance 50% at 40°C Calculated 100000 Lumen Maintenance 50% at 40°C Reported 60000 Lumen Maintenance 70% at 25°C Calculated 100000 Lumen Maintenance 70% at 25°C Reported 60000 Lumen Maintenance 70% at 40°C Calculated 100000 |
|--|
| Lumen Maintenance 50% at 40°C Calculated 100000 Lumen Maintenance 50% at 40°C Reported 60000 Lumen Maintenance 70% at 25°C Calculated 100000 Lumen Maintenance 70% at 25°C Reported 60000 |
| Lumen Maintenance 50% at 40°C Reported 60000 Lumen Maintenance 70% at 25°C Calculated 100000 Lumen Maintenance 70% at 25°C Reported 60000 |
| Lumen Maintenance 70% at 25°C Calculated 100000 Lumen Maintenance 70% at 25°C Reported 60000 |
| Lumen Maintenance 70% at 25°C Reported 60000 |
| · · · · · · · · · · · · · · · · · · · |
| Lumen Maintenance 70% at 40°C Calculated 100000 |
| |
| Lumen Maintenance 70% at 40°C Reported 60000 |


| Product Data | |
|---------------------------------|--------------------------|
| Order product name | BCP431 RGB 100-240 20 UL |
| EAN/UPC - Product | 8718291647102 |
| Order code | 912400133974 |
| Local order code | |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 4 |
| Material Nr. (12NC) | 912400133974 |
| Net Weight (Piece) | 2.800 kg |
| | |

| IK 06 |
|-------|
|-------|

Application Conditions

Ambient temperature range -40 to +104 °F

Dimensional drawing



Vaya

