

Vaya Flood MP Medium

BCP434 RGB 100-240 10 CE CQC PSE

Vaya Flood MP G2, RGB, 10°, CE/CQC/PSE

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures.Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colorful lighting effects that can bring a property to life.The robust Vaya Flood offers a wide choice of mono colors with a simple on-off switch and changing colors with a standard DMX512 controller. It is also extremely easy to install and aim.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Red, green and blue
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Protection class IEC	Safety class I (I)
CE mark	CE mark
CQC mark	CQC-mark
Optic type outdoor	Narrow beam angle 10°
PSE mark	PSE mark
Angle	10°

Operating and Electrical	
Input Voltage	100 to 240 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Housing material	Aluminum die-cast
Optic material	Glass
Optical cover/lens material	Glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Colour	Dark gray

Vaya Flood MP Medium

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Energy Efficiency Class	G
Mech. impact protection code	IK06 [1 J]
Vibration standard	Complies with ANSI C136.31
Vibration rating	Complies with ANSI C136.31
	991203

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	2603 lm
Initial LED luminaire efficacy	37 lm/W
Initial input power	72 W


Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25 °C Calculated	100000
Lumen Maintenance 50% at 25 °C Reported	60000
Lumen Maintenance 50% at 40 °C Calculated	100000
Lumen Maintenance 50% at 40 °C Reported	60000
Lumen Maintenance 70% at 25 °C Calculated	100000
Lumen Maintenance 70% at 25 °C Reported	60000
Lumen Maintenance 70% at 40 °C Calculated	100000
Lumen Maintenance 70% at 40 °C Reported	60000

Application Conditions	
Ambient temperature range	-40 to +40 °C

Product Data	
Full product code	871829164980999
Order product name	BCP434 RGB 100-240 10 CE CQC PSE
EAN/UPC – product	8718291649809
Order code	316-000016-00
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	912400133977
SAP net weight (piece)	5.250 kg
Commercial Code	316-000016-00
Catalogue number description	Vaya Flood MP G2, RGB, 10°, CE/CQC/PSE

IP66 IK06

Dimensional drawing



Vaya

© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.