PHILIPS Lighting



Vaya Flood MP Medium

BCP434 RGB 100-240 20 CE CQC PSE

Medium beam angle 20°

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures.Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colorful lighting effects that can bring a property to life.The robust Vaya Flood offers a wide choice of mono colors with a simple on-off switch and changing colors with a standard DMX512 controller. It is also extremely easy to install and aim.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source color	Red, green and blue (RGB)
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Protection class IEC	Safety class I (I)
CE mark	CE mark
CQC mark	CQC-mark
Optic type outdoor	Medium beam angle 20°
PSE mark	PSE mark
Angle	20°
Operating and Electrical	
Input Voltage	100 to 240 V
Input Frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum die-cast
Optic material	Glass
Optical cover/lens material	Glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	2567 lm
Initial LED luminaire efficacy	35.4 lm/W

Vaya Flood MP Medium

Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25°C Calculated	100000	
Lumen Maintenance 50% at 25°C Reported	60000	
Lumen Maintenance 50% at 40°C Calculated	100000	
Lumen Maintenance 50% at 40°C Reported	60000	
Lumen Maintenance 70% at 25°C Calculated	100000	
Lumen Maintenance 70% at 25°C Reported	60000	
Lumen Maintenance 70% at 40°C Calculated	100000	
Lumen Maintenance 70% at 40°C Reported	60000	

-40 to +104 °F


Application Conditions

Ambient temperature range

Product Data BCP434 RGB 100-240 20 CE CQC PSE Order product name EAN/UPC - Product 8718291649816 Order code 912400133978 Local order code Numerator - Quantity Per Pack 1 Numerator - Packs per outer box 2 Material Nr. (12NC) 912400133978 Net Weight (Piece) 5.250 kg

IK 06

Dimensional drawing





© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, December 3 - data subject to change