



# Vaya Flood MP

BCP434 RGB 100-240 20 CE CQC PSE

Medium beam angle 20°

Vaya Flood MP gen2 is a reliable and cost effective LED flood lighting solution for both interior and exterior use that minimizes the initial investment, while providing exceptional flexibility to create eye-catching flood, wash and accent lighting effects. A wide choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.

## Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [ LED High Brightness]	Dimmable	Yes
Light source color	Red, green and blue		
Light source replaceable	No		
Driver included	Yes		
Optical cover/lens type	Tempered glass		
Protection class IEC	Safety class I		
CE mark	CE mark		
CQC mark	CQC-mark		
Optic type outdoor	Medium beam angle 20°		
PSE mark	PSE mark		
Angle	20°		
Operating and Electrical		Mechanical and Housing	
Input Voltage	100 to 240 V	Housing Material	Aluminum die cast
Input Frequency	50 to 60 Hz	Optic material	Glass
		Optical cover/lens material	Glass
		Optical cover/lens shape	Flat
		Optical cover/lens finish	Clear
		Color	Dark gray
		Approval and Application	
		Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
		Mech. impact protection code	IK06 [ 1 J]
		Vibration Standard	Complies with ANSI C136.31
		Vibration Rating	Complies with ANSI C136.31


Vaya Flood MP

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	2567 lm
Initial LED luminaire efficacy	35.4 lm/W
Initial input power	72 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25°C Calculated	100000
Lumen Maintenance 50% at 25°C Reported	60000
Lumen Maintenance 50% at 40°C Calculated	100000
Lumen Maintenance 50% at 40°C Reported	60000
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	100000
Lumen Maintenance 70% at 40°C Reported	60000

Application Conditions	
Ambient temperature range	-40 to +40 °C
Product Data	
Full product code	871829164981699
Order product name	BCP434 RGB 100-240 20 CE CQC PSE
EAN/UPC - Product	8718291649816
Order code	912400133978
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	912400133978
Net Weight (Piece)	5.250 kg



Dimensional drawing



Vaya

