



Vaya Flood MP

BCP435 3000 220-240 20 CE CQC

Medium beam angle 20°

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures. Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colourful lighting effects that can bring a property to life. The robust Vaya Flood offers a wide choice of mono colours with a simple on-off switch and changing colours with a standard DMX512 controller. It is also extremely easy to install and aim.

Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [LED High Brightness]	Dimmable	Yes
Lamp colour code	Neutral white	Mechanical and Housing	
Light source replaceable	No	Housing material	Aluminum die-cast
Driver included	Yes	Optic material	Glass
Optical cover/lens type	GT [Tempered glass]	Optical cover/lens material	Glass
Luminaire light beam spread	20°	Optical cover/lens shape	Flat
Protection class IEC	Safety class I (I)	Optical cover/lens finish	Clear
CE mark	CE mark	Colour	Dark Grey
CQC mark	CQC-mark	Approval and Application	
Outdoor optic type	Medium beam angle 20°	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
PSE mark	No	Mech. impact protection code	IK06 [1 J]
Angle	20°	Vibration standard	Complies with ANSI C136.31
Operating and Electrical			Complies with ANSI C136.31
Input voltage	220 to 240 V		
Input frequency	50 to 60 Hz		

Vaya Flood MP

Initial Performance (IEC Compliant)

Initial luminous flux	5660 lm
Initial LED luminaire efficacy	83.5 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	80
Initial input power	68 W

Over Time Performance (IEC Compliant)

Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	71000
Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	100000
Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	45000
Lumen Maintenance 80% at 40°C Reported	45000
Lumen Maintenance 90% at 25°C Calculated	74000
Lumen Maintenance 90% at 25°C Reported	60000

Lumen Maintenance 90% at 40°C Calculated	23000
Lumen Maintenance 90% at 40°C Reported	23000

Application Conditions


Ambient temperature range	-40 to +40 °C
---------------------------	---------------

Product Data

Full product code	871829164993999
Order product name	BCP435 3000 220-240 20 CE CQC
EAN/UPC – product	8718291649939
Order code	912400134021
Numerator – quantity per pack	1
Numerator – packs per outer box	2
Material no. (12NC)	912400134021
Net weight (piece)	5.720 kg



Dimensional drawing



Vaya

