



# Vaya Flood MP G2, White

## Vaya Flood MP G2, 4000 K, 20°, CE/CQC

Vaya Flood MP G2, 4000 K, 20°, CE/CQC

Vaya Flood MP (gen2) is a reliable and cost effective LED flood lighting solution for both exterior use that minimizes the initial investment, while providing exceptional flexibility to create eye-catching flood, wash and accent lighting effects. A wide choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.

### Product data

General information		Operating and electrical	
Lamp family code	LED-HB [ LED High Brightness]	Input Voltage	220 to 240 V
Light source color	Neutral white	Input Frequency	50 to 60 Hz
Light source replaceable	No		
Driver included	Yes	Controls and dimming	
Optical cover/lens type	Tempered glass	Dimmable	Yes
Luminaire light beam spread	20°		
Protection class IEC	Safety class I	Mechanical and housing	
CE mark	CE mark	Housing Material	Aluminum die cast
CQC mark	CQC-mark	Optic material	Glass
Optic type outdoor	Medium beam angle 20°	Optical cover/lens material	Glass
PSE mark	No	Optical cover/lens shape	Flat
Angle	20°	Optical cover/lens finish	Clear
		Color	Dark gray

# Vaya Flood MP G2, White

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]
Vibration Standard	Complies with ANSI C136.31
Vibration Rating	Complies with ANSI C136.31

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	6150 lm
Initial luminous flux at color temperature of 4000 K	6150 lm
Initial LED luminaire efficacy	90.8 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	82
Initial input power	68 W

## Over time performance (IEC compliant)

Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	71000
Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	100000
Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	45000


Lumen Maintenance 80% at 40°C Reported	45000
Lumen Maintenance 90% at 25°C Calculated	74000
Lumen Maintenance 90% at 25°C Reported	60000
Lumen Maintenance 90% at 40°C Calculated	23000
Lumen Maintenance 90% at 40°C Reported	23000

## Application conditions


Ambient temperature range	-40 to +40 °C
---------------------------	---------------

## Product data

Full product code	871829138600199
Order product name	BCP435 4000 220-240 20 CE CQC
EAN/UPC - Product	8718291386001
Order code	350-000016-09
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	912400134024
Net Weight (Piece)	6.775 kg
Catalog Number	350-000016-09
Catalog Number Description	Vaya Flood MP G2, 4000 K, 20°, CE/CQC



## Dimensional drawing



BCP435 4000 220-240 20 CE CQC

