



# Vaya Flood MP Medium

## BCP435 2700 220-240 10 CE CQC

Narrow beam angle 10°

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures. Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colorful lighting effects that can bring a property to life. The robust Vaya Flood offers a wide choice of mono colors with a simple on-off switch and changing colors with a standard DMX512 controller. It is also extremely easy to install and aim.

#### **Product data**

| General Information      |                               |
|--------------------------|-------------------------------|
| Lamp family code         | LED-HB [ LED High Brightness] |
| Light source color       | Cool white                    |
| Light source replaceable | No                            |
| Driver included          | Yes                           |
| Optical cover/lens type  | GT [ Tempered glass]          |
| Protection class IEC     | Safety class I (I)            |
| CE mark                  | CE mark                       |
| CQC mark                 | CQC-mark                      |
| Optic type outdoor       | Narrow beam angle 10°         |
| PSE mark                 | No                            |
| Angle                    | 10°                           |
|                          |                               |
| Operating and Electrical |                               |
| Input Voltage            | 220 to 240 V                  |

| Input Frequency             | 50 to 60 Hz       |  |
|-----------------------------|-------------------|--|
|                             |                   |  |
| Controls and Dimming        |                   |  |
| Dimmable                    | Yes               |  |
|                             |                   |  |
| Mechanical and Housing      |                   |  |
| Housing Material            | Aluminum die–cast |  |
| Optic material              | Glass             |  |
| Optical cover/lens material | Glass             |  |
| Optical cover/lens shape    | Flat              |  |
| Optical cover/lens finish   | Clear             |  |
| Color                       | Dark gray         |  |

Datasheet, 2019, May 2 data subject to change


# Vaya Flood MP Medium

| Approval and Application                 |   |  |
|--|---|--|
| Ingress protection code                  | IP66 [ Dust penetration-protected, jet- |  |
|  | proof]                                  |  |
| Mech. impact protection code             | IK06 [1J]                               |  |
|  |   |  |
| Initial Performance (IEC Compliant)      |   |  |
| Init. Corr. Color Temperature            | 2700 K                                  |  |
|  |   |  |
| Over Time Performance (IEC Compliant)    |   |  |
| Lumen Maintenance 70% at 25°C Calculated | 100000                                  |  |
| Lumen Maintenance 70% at 25°C Reported   | 60000                                   |  |
| Lumen Maintenance 70% at 40°C Calculated | 71000                                   |  |
| Lumen Maintenance 70% at 40°C Reported   | 60000                                   |  |
| Lumen Maintenance 80% at 25°C Calculated | 100000                                  |  |
| Lumen Maintenance 80% at 25°C Reported   | 60000                                   |  |
| Lumen Maintenance 80% at 40°C Calculated | 45000                                   |  |
| Lumen Maintenance 80% at 40°C Reported   | 45000                                   |  |
| Lumen Maintenance 90% at 25°C Calculated | 74000                                   |  |
| Lumen Maintenance 90% at 25°C Reported   | 60000                                   |  |

| Lumen Maintenance 90% at 40°C Calculated 23000 |                               |  |  |
|--|-------------------------------|--|--|
| Lumen Maintenance 90% at 40°C Reported         | 23000                         |  |  |
|  |                               |  |  |
| Application Conditions                         |                               |  |  |
| Ambient temperature range                      | -40 to +40 °C                 |  |  |
|  |                               |  |  |
| Product Data                                   |                               |  |  |
| Full product code                              | 871829138608799               |  |  |
| Order product name                             | BCP435 2700 220-240 10 CE CQC |  |  |
| EAN/UPC - Product                              | 8718291386087                 |  |  |
| Order code                                     | 912400134032                  |  |  |
| Numerator - Quantity Per Pack                  | 1                             |  |  |
| Numerator - Packs per outer box                | 2                             |  |  |
| Material Nr. (12NC)                            | 912400134032                  |  |  |
| Net Weight (Piece)                             | 5.720 kg                      |  |  |
|  |                               |  |  |



### Dimensional drawing



Vaya



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.