PHILIPS Lighting



Vaya Flood MP

BCP435 5000 220-240 40 CE CQC

Medium beam angle 40°

With budgets under pressure, property owners and developers are looking, more than ever, for value for money when it comes to capital expenditures.Vaya Flood is an affordable and reliable LED solution that minimizes the initial investment, while providing exceptional flexibility to create eye-catching, dynamic and colourful lighting effects that can bring a property to life.The robust Vaya Flood offers a wide choice of mono colours with a simple on-off switch and changing colours with a standard DMX512 controller. It is also extremely easy to install and aim.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Lamp colour code	Cool white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Luminaire light beam spread	40°
Protection class IEC	Safety class I (I)
CE mark	CE mark
CQC mark	CQC-mark
Outdoor optic type	Medium beam angle 40°
PSE mark	No
Angle	40°
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum die–cast
Optic material	Glass
Optical cover/lens material	Glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Colour	Dark Grey
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK06 [1 J]


Vaya Flood MP

Initial Performance (IEC Compliant)		
Lamp colour temperature	5000 K	
Over Time Performance (IEC Complian	t)	
Lumen Maintenance 70% at 25°C Calculated	100000	
Lumen Maintenance 70% at 25°C Reported	60000	
Lumen Maintenance 70% at 40°C Calculated	71000	
Lumen Maintenance 70% at 40°C Reported	60000	
Lumen Maintenance 80% at 25°C Calculated	100000	
Lumen Maintenance 80% at 25°C Reported	60000	
Lumen Maintenance 80% at 40°C Calculated	45000	
Lumen Maintenance 80% at 40°C Reported	45000	
Lumen Maintenance 90% at 25°C Calculated	74000	
Lumen Maintenance 90% at 25°C Reported	60000	
Lumen Maintenance 90% at 40°C Calculated	23000	
Lumen Maintenance 90% at 40°C Reported	23000	

Application Conditions	
Ambient temperature range	-40 to +40 °C
Product Data	
Full product code	871829138616299
Order product name	BCP435 5000 220-240 40 CE CQC
EAN/UPC – product	8718291386162
Order code	912400134040
Numerator – quantity per pack	1
Numerator – packs per outer box	2
Material no. (12NC)	912400134040
Net weight (piece)	5.720 kg

IK 06

Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, May 2 - data subject to change