PHILIPS

Lighting



eW Graze MX Powercore

eW Graze MX Powercore, 3000 K, 30° x 60° Beam Angle, 610 mm (2 ft)

eW Graze MX Powercore, 3000 K, 30° x 60° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	White
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	30° x 60°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 50% luminous flux	60000 h
Lifetime to 70% luminous flux	60000 h

Operating and electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing material	Aluminum extruded
Optical cover/lens material	Polycarbonate
Length	609 mm

eW Graze MX Powercore

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G

Initial performance (IEC compliant)	
Init. Corr. Colour Temperature	3000 K
Initial input power	28 W


Over time performance (IEC compliant)	
Lumen Maintenance 50% at 25 °C Reported	60000
Lumen Maintenance 50% at 50 °C Reported	60000
Lumen Maintenance 70% at 25 °C Reported	60000
Lumen Maintenance 70% at 50 °C Reported	60000

Application conditions	
Ambient temperature range	-20 to +50 °C

Product data	
Full product code	871829139509699
Order product name	BCS419 30x60-3000 L609
EAN/UPC – product	8718291395096
Order code	523-000080-68
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	912400135121
Net Weight (Piece)	2.700 kg
Commercial Code	523-000080-68
Catalogue number description	eW Graze MX Powercore, 3000 K, 30° x 60° Beam Angle, 610 mm (2 ft)



Dimensional drawing



BCS419 30x60-3000 L609

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.