



eW Graze MX Powercore

eW Graze MX Powercore, 3000 K, 60° x 30° Beam Angle, 610 mm (2 ft)

eW Graze MX Powercore, 3000 K, 60° x 30° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

| | | | |
|---------------------------------|-------------------------------|---|--|
| General information | | Input frequency | |
| Lamp family code | LED-HB [LED High Brightness] | 50 to 60 Hz | |
| Light source colour | White | Controls and dimming | |
| Light source replaceable | No | Dimmable | |
| Luminaire light beam spread | 60° x 30° | Yes | |
| Protection class IEC | Safety class I (I) | Mechanical and housing | |
| CE mark | CE mark | Housing material | |
| UL mark | UL and cUL mark | Aluminum extruded | |
| Lifetime to 50% luminous flux | 60000 h | Optical cover/lens material | |
| Lifetime to 70% luminous flux | 60000 h | Polycarbonate | |
| Operating and electrical | | Length | |
| Input Voltage | 100 to 277 V | Approval and application | |
| | | Ingress protection code | |
| | | IP66 [Dust penetration-protected, jet-proof] | |

eW Graze MX Powercore

| | |
|------------------------------|--------------------------------|
| Mech. impact protection code | IK10 [20 J vandal-resistant] |
| Vibration standard | Complies with ANSI C136.31, 3G |
| FCC mark | FCC Class A |
| Vibration rating | Complies with ANSI C136.31, 3G |

Initial performance (IEC compliant)

| | |
|--------------------------------|--------|
| Init. Corr. Colour Temperature | 3000 K |
| Initial input power | 28 W |

Over time performance (IEC compliant)

| | |
|---|-------|
| Lumen Maintenance 50% at 25 °C Reported | 60000 |
| Lumen Maintenance 50% at 50 °C Reported | 60000 |
| Lumen Maintenance 70% at 25 °C Reported | 60000 |
| Lumen Maintenance 70% at 50 °C Reported | 60000 |

Application conditions

| | |
|---------------------------|---------------|
| Ambient temperature range | -20 to +50 °C |
|---------------------------|---------------|

| | |
|-----------------------------------|---|
| Product data | |
| Full product code | 871829139510299 |
| Order product name | BCS419 60x30-3000 L609 |
| EAN/UPC – product | 8718291395102 |
| Order code | 523-000080-69 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 4 |
| SAP material | 912400135122 |
| Net Weight (Piece) | 2.700 kg |
| Commercial Code | 523-000080-69 |
| Catalogue number description | eW Graze MX Powercore, 3000 K, 60° x 30° Beam Angle, 610 mm (2 ft) |



Dimensional drawing

