



eW Graze MX Powercore

eW Graze MX Powercore, 3000 K, 60° x 30° Beam Angle, 610 mm (2 ft)

eW Graze MX Powercore, 3000 K, 60° x 30° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General information		Input frequency	
Lamp family code	LED-HB [LED High Brightness]	50 to 60 Hz	
Light source colour	White	Controls and dimming	
Light source replaceable	No	Dimmable	
Luminaire light beam spread	60° x 30°	Yes	
Protection class IEC	Safety class I	Mechanical and housing	
CE mark	CE mark	Housing material	
UL mark	UL and cUL mark	Extruded aluminium	
Lifetime to 50% luminous flux	60000 h	Optical cover/lens material	
Lifetime to 70% luminous flux	60000 h	Polycarbonate	
Operating and electrical		Length	
Input Voltage	100 to 277 V	Approval and application	
		Ingress protection code	
		IP66 [Dust penetration-protected, jet-proof]	

eW Graze MX Powercore

Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
FCC mark	FCC Class A
Vibration rating	Complies with ANSI C136.31, 3G
Initial performance (IEC compliant)	
Init. Corr. Colour Temperature	3000 K
Initial input power	28 W
Over time performance (IEC compliant)	
Lumen Maintenance 50% at 25 °C Reported	60000
Lumen Maintenance 50% at 50 °C Reported	60000
Lumen Maintenance 70% at 25 °C Reported	60000
Lumen Maintenance 70% at 50 °C Reported	60000
Application conditions	
Ambient temperature range	-20 to +50 °C

Product data	
Full product code	871829139510299
Order product name	BCS419 60x30-3000 L609
EAN/UPC – product	8718291395102
Order code	523-000080-69
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	912400135122
Net Weight (Piece)	2.700 kg
Commercial Code	523-000080-69
Catalogue number description	eW Graze MX Powercore, 3000 K, 60° x 30° Beam Angle, 610 mm (2 ft)



Dimensional drawing

