



# eW Graze MX Powercore

## BCS419 15x30-3500 L305

eW Graze MX Powercore, 3500 K,  $15^{\circ}$  x  $30^{\circ}$  Beam Angle, 305 mm (1 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

#### **Product data**

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Light source colour	Neutral white
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	15° x 30°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 50% luminous flux	60000 h
Lifetime to 70% luminous flux	60000 h
	-
Operating and Electrical	-
Input Voltage	100 to 277 V

Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum extruded
Optical cover/lens material	Polycarbonate
Length	305 mm
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-
	proof]
Vibration standard	Complies with ANSI C136.31, 3G

Datasheet, 2022, February 21 data subject to change

## **eW Graze MX Powercore**

Vibration rating	Complies with ANSI C136.31, 3G	
Initial Performance (IEC Compliant)		
Init. Corr. Colour Temperature	3500 K	
Init. Colour rendering index	>80	
Initial input power	15 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25 °C Reported	60000	
Lumen Maintenance 50% at 50 °C Reported 60000		
Lumen Maintenance 70% at 25 °C Reported	60000	
Lumen Maintenance 70% at 50 °C Reported 60000		
Application Conditions		


-20 to +50 ℃

871829139513399
BCS419 15x30-3500 L305
8718291395133
523-000080-82
1
4
912400135135
1.200 kg
523-000080-82
eW Graze MX Powercore, 3500 K, 15° x 30°
Beam Angle, 305 mm (1 ft)



### Dimensional drawing

Ambient temperature range



BCS419 15x30-3500 L305



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.