



eW Graze EC Powercore

BCS428 3500 WB L1220

eW Graze EC Powercore, 3500 K, 90° x 90° Beam Angle, 1219 mm (4 ft)

Some exterior architectural details require a soft-edged volume fill of light. Graze EC Powercore combines this output with the proven, durable design of the Graze Powercore product family and low power consumption.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	White
Light source replaceable	No
Optical cover/lens type	PCF [Polycarbonate bowl/cover frosted]
Luminaire light beam spread	90° x 90°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	36000 h
Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Housing material	Extruded aluminium
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	1220 mm
Colour	Aluminium
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Ingress protection code Mech. impact protection code	IP66 [Dust penetration-protected, jet-proof] IK10 [20 J vandal-resistant]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Mech. impact protection code	IK10 [20 J vandal-resistant] Not compliant to ANSI C136.31, 3G. Special
Mech. impact protection code	IK10 [20 J vandal-resistant] Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the
Mech. impact protection code	IK10 [20 J vandal-resistant] Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics
Mech. impact protection code Vibration standard	IK10 [20 J vandal-resistant] Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations.

Datasheet, 2022, February 21 data subject to change

eW Graze EC Powercore


	standard. Please contact your Color Kinetics
	Lighting Sales rep for custom configurations.
Initial Performance (IEC Complia	ant)
Init. Corr. Colour Temperature	3500 K
Init. Colour rendering index	82
Initial input power	20 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25 °C	36000
Reported	
Lumen Maintenance 50% at 50 °C	36000
Reported	
Lumen Maintenance 70% at 25 °C	36000
Reported	
Lumen Maintenance 70% at 50 °C	36000
Reported	

Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871869921011300
Order product name	BCS428 3500 WB L1220
EAN/UPC - product	8718699210113
Order code	523-000082-19
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	912400135334
SAP net weight (piece)	4.700 kg
Commercial Code	523-000082-19
Catalogue number description	eW Graze EC Powercore, 3500 K, 90° x 90°
	Beam Angle, 1219 mm (4 ft)





Dimensional drawing



BCS428 3500 WB L1220



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.