



Flex Compact, iW

iW Flex Compact, Clear Flat Lens, Black Housing, 4 in On-Center Node Spacing

iW Flex Compact, Clear Flat Lens, Black Housing, 4 in On-Center Node Spacing

iW Flex Compact are flexible strands of large, high-intensity, tunable-white LED nodes designed for extraordinary effects and expansive installations without the constraints of luminaire size, shape, or space. Each iW Flex Compact strand consists of 50 individually addressable LED nodes, featuring dynamic integration of power, communication, and control. The flexible form factor accommodates two- and three-dimensional configurations, while high light output affords superior long-distance viewing for architectural accent and perimeter lighting, large-scale signage, and building-covering video displays.

Product data

General information		Approval and application	
Light source color	Cool white and warm white	FCC mark	FCC Class A
Optical cover/lens type	Clear flat 4 inch separated	Initial performance (IEC compliant)	
Luminaire light beam spread	105°	Initial input power	1 W
Light technical		Over time performance (IEC compliant)	
Light source flux per node	80 lm	Lumen Maintenance 50% at 25°C Calculated	100000
On-axis intensity in candela	31.4	Lumen Maintenance 50% at 25°C Reported	60000
CRI @ 6500 K	83.4	Lumen Maintenance 50% at 50°C Calculated	100000
CRI @ 2700	82.1	Lumen Maintenance 50% at 50°C Reported	60000
Mechanical and housing		Lumen Maintenance 70% at 25°C Calculated	56000
Color	White	Lumen Maintenance 70% at 25°C Reported	56000
		Lumen Maintenance 70% at 50°C Calculated	56000

Flex Compact, iW

Lumen Maintenance 70% at 50°C Reported	56000
Product data	
Full product code	871869921469299
Order product name	BGC481 50 2700-6500K CLFT BK P102
EAN/UPC - Product	8718699214692
Order code	501-000016-01
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	6
Material Nr. (12NC)	912400135816
Net Weight (Piece)	0.750 kg
Catalog Number	501-000016-01
Catalog Number Description	iW Flex Compact, Clear Flat Lens, Black Housing, 4 in On-Center Node Spacing

