PHILIPS

Lighting



Flex Compact, iW

iW Flex Compact, Translucent Dome Lens, White Housing, 12 in On-Center Node Spacing

iW Flex Compact, Translucent Dome Lens, White Housing, 12 in On-Center Node Spacing

iW Flex Compact are flexible strands of large, high-intensity, tunable-white LED nodes designed for extraordinary effects and expansive installations without the constraints of luminaire size, shape, or space. Each iW Flex Compact strand consists of 50 individually addressable LED nodes, featuring dynamic integration of power, communication, and control. The flexible form factor accommodates two- and three-dimensional configurations, while high light output affords superior long-distance viewing for architectural accent and perimeter lighting, large-scale signage, and building-covering video displays.

Product data

General information	
Light source color	Cool white and warm white
Optical cover/lens type	Transparent dome 12 inch separated
Luminaire light beam spread	165°

Light technical	
Light source flux per node	28 lm
On-axis intensity in candela	4.9
CRI @ 6500 K	88.5
CRI @ 2700	86.2

Mechanical and housing	
Color	White

Approval and application	
FCC mark	FCC Class A

Initial performance (IEC compliant)	
Initial input power	1 W

Over time performance (IEC compliant)	
Lumen Maintenance 50% at 25°C Calculated	100000
Lumen Maintenance 50% at 25°C Reported	60000
Lumen Maintenance 50% at 50°C Calculated	100000
Lumen Maintenance 50% at 50°C Reported	60000
Lumen Maintenance 70% at 25°C Calculated	56000
Lumen Maintenance 70% at 25°C Reported	56000
Lumen Maintenance 70% at 50°C Calculated	56000

Flex Compact, iW

Lumen Maintenance 70% at 50°C Reported	56000

Product data

Full product code	871869921474699
Order product name	BGC481 50 2700-6500K TSDM WH P305
EAN/UPC - Product	8718699214746
Order code	501-000016-06
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6

Material Nr. (12NC)	912400135821
Net Weight (Piece)	0.750 kg
Catalog Number	501-000016-06
Catalog Number Description	iW Flex Compact, Translucent Dome Lens, White Housing, 12 in On-Center Node Spacing

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.