



eW Profile Powercore gen4

eW Profile Powercore gen4, 3000 K, 220 – 240 VAC, 997 mm (39.25 in)

eW Profile Powercore gen4, 3000 K, 220 – 240 VAC, 997 mm (39.25 in)

Profile gen4 brings advanced under-cabinet lighting to today's sophisticated kitchens. Thanks to its ultra-low profile, Profile gen4 fits seamlessly into any kitchen —from galley to grand, including retrofits and new construction. To create the right ambiance, it offers four popular color temperatures (2700 K, 3000 K, 3500 K, or 4000 K). A choice of luminaire lengths and a wide range of accessories keep installation fast and easy. Exceptional energy efficiency can generate rebates right from the start, and deliver dramatic energy savings over many years of reliable use.

Product data


| General information | | Over time performance (IEC compliant) |
|-------------------------------------|--------------------------|-------------------------------------------------|
| Optic type | Wide beam | Lumen Maintenance 50% at 25°C Calculated 100000 |
| Optical cover/lens type | Polycarbonate bowl/cover | Lumen Maintenance 50% at 25°C Reported 60000 |
| Luminaire light beam spread | 105° | Lumen Maintenance 50% at 50°C Calculated 100000 |
| | | Lumen Maintenance 50% at 50°C Reported 60000 |
| Mechanical and housing | | Lumen Maintenance 70% at 25°C Calculated 100000 |
| Color | White | Lumen Maintenance 70% at 25°C Reported 60000 |
| | | Lumen Maintenance 70% at 50°C Calculated 100000 |
| Initial performance (IEC compliant) | | Lumen Maintenance 70% at 50°C Reported 60000 |
| Init. Corr. Color Temperature | 3000 K | Lumen Maintenance 80% at 25°C Calculated 86000 |
| Initial input power | 11 W | Lumen Maintenance 80% at 25°C Reported 60000 |
| | | Lumen Maintenance 80% at 50°C Calculated 65000 |

eW Profile Powercore gen4

| Lumen Maintenance 80% at 50°C Reported | 60000 | | | |
|------------------------------------------------|--------------------------|--|--|--|
| Lumen Maintenance 90% at 25°C Calculated | 41000 | | | |
| Lumen Maintenance 90% at 25°C Reported | 41000 | | | |
| Lumen Maintenance 90% at 50°C Calculated 30000 | | | | |
| Lumen Maintenance 90% at 50°C Reported | 30000 | | | |
| | | | | |
| Product data | | | | |
| Full product code | 871869921373299 | | | |
| Order product name | BCX413 3000 230V 997L WH | | | |
| EAN/UPC - Product | 8718699213732 | | | |

| 523-000102-05 | |
|----------------------------------------|--|
| 1 | |
| 6 | |
| 912400135977 | |
| 0.836 kg | |
| 523-000102-05 | |
| eW Profile Powercore gen4, 3000 K, 220 | |
| 240 VAC, 997 mm (39.25 in) | |
| | |

Dimensional drawing



BCX413 3000 230V 997L WH



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2022, September 15 - data subject to change