



# Vaya Linear LP G2, White

## Vaya Linear LP G2, 3000 K, 120°, 1.2 m (4 ft), UL

Vaya Linear LP G2, 3000 K, 120°, 1.2 m (4 ft), UL

Vaya Linear LP is a super slim outdoor linear luminaire for low-level grazing applications, with wide 120° beam or elliptical 28° x 84° optics. Its slim form factor is ideal for space-restricted applications with limited setback or allowable install height. The robust Vaya Linear LP G2 offers a variety of color and white CCT options with static on/off control. Dynamic control options via standard DMX-512 are available by custom order. The discreet design with integrated power supply and waterproof connectors makes wiring simple, fast and reliable.

### Product data

General information	
Lamp family code	LED-HB [ LED High Brightness]
Light source color	Neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Tempered glass
Luminaire light beam spread	120°
CE mark	-
UL mark	UL and cUL mark
CQC mark	-
PSE mark	No
Operating and electrical	
Input Voltage	100 to 240 V
Mechanical and housing	
Input Frequency	50 to 60 Hz
Housing Material	Aluminum extruded
Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Color	Dark gray
Approval and application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]
Vibration Standard	Complies with ANSI C136.31

Vaya Linear LP G2, White

FCC mark	FCC Class A
Vibration Rating	Complies with ANSI C136.31

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1480 lm
Initial LED luminaire efficacy	84.3 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	82
Initial input power	17.6 W

Over time performance (IEC compliant)

Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	100000
Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	87000
Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	66000
Lumen Maintenance 80% at 40°C Reported	60000
Lumen Maintenance 90% at 25°C Calculated	41000
Lumen Maintenance 90% at 25°C Reported	41000

Lumen Maintenance 90% at 40°C Calculated	31000
Lumen Maintenance 90% at 40°C Reported	31000

Application conditions

Ambient temperature range	-40 to +40 °C
---------------------------	---------------

Product data

Full product code	871869921816499
Order product name	BCP422 G2 120 3000 L1200 UL
EAN/UPC - Product	8718699218164
Order code	350-000018-10
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	912400136128
Net Weight (Piece)	1.860 kg
Catalog Number	350-000018-10
Catalog Number Description	Vaya Linear LP G2, 3000 K, 120°, 1.2 m (4 ft), UL

