



# Vaya Linear LP G2, White

Vaya Linear LP G2, 3000 K, 28° x 84°, 1.2 m (4 ft), UL

Vaya Linear LP G2, 3000 K, 28° x 84°, 1.2 m (4 ft), UL

Vaya Linear LP is a super slim outdoor linear luminaire for low-level grazing applications, with wide 120° beam or elliptical 28° x 84° optics. Its slim form factor is ideal for space-restricted applications with limited setback or allowable install height. The robust Vaya Linear LP G2 offers a variety of color and white CCT options with static on/off control. Dynamic control options via standard DMX-512 are available by custom order. The discreet design with integrated power supply and waterproof connectors makes wiring simple, fast and reliable.

## Product data

<b>General information</b>		<b>Input Frequency</b>	
Lamp family code	LED-HB [ LED High Brightness]	50 to 60 Hz	
Light source color	Neutral white	<b>Mechanical and housing</b>	
Light source replaceable	No	<b>Housing Material</b>	
Driver included	Yes	Aluminum extruded	
Optical cover/lens type	Tempered glass	<b>Optic material</b>	
CE mark	-	Glass	
UL mark	UL and cUL mark	<b>Optical cover/lens material</b>	
CQC mark	-	Tempered glass	
PSE mark	No	<b>Optical cover/lens shape</b>	
<b>Operating and electrical</b>		<b>Optical cover/lens finish</b>	
Input Voltage	100 to 240 V	Clear	
		<b>Color</b>	
		Dark gray	
		<b>Approval and application</b>	
		<b>Ingress protection code</b>	
		IP66 [ Dust penetration-protected, jet-proof]	
		<b>Mech. impact protection code</b>	
		IK07 [ 2 J reinforced]	

Vaya Linear LP G2, White

Vibration Standard	Complies with ANSI C136.31
FCC mark	FCC Class A
Vibration Rating	Complies with ANSI C136.31

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1712 lm
Initial LED luminaire efficacy	98.8 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	82
Initial input power	17.4 W

Over time performance (IEC compliant)

Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	100000
Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	87000
Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	66000
Lumen Maintenance 80% at 40°C Reported	60000
Lumen Maintenance 90% at 25°C Calculated	41000
Lumen Maintenance 90% at 25°C Reported	41000

Lumen Maintenance 90% at 40°C Calculated	31000
Lumen Maintenance 90% at 40°C Reported	31000

Application conditions

Ambient temperature range	-40 to +40 °C
---------------------------	---------------

Product data

Full product code	871869921817199
Order product name	BCP422 G2 28x84 3000 L1200 UL
EAN/UPC - Product	8718699218171
Order code	350-000018-11
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	912400136129
Net Weight (Piece)	2.150 kg
Catalog Number	350-000018-11
Catalog Number Description	Vaya Linear LP G2, 3000 K, 28° x 84°, 1.2 m (4 ft), UL

