PHILIPS Lighting



Vaya Linear LP G2

BCP422 G2 120 2700 L610 CE CQC PSE

LED High Brightness

Vaya Linear LP is a super slim outdoor linear luminaire for low-level grazing applications, with wide 120° beam or elliptical 28° x 84° optics. Its slim form factor is ideal for space-restricted applications with limited set-back or allowable install height. The robust Vaya Linear LP G2 offers a variety of colour and white CCT options with either static on/off- or dynamic control options via standard DMX-512. The discreet design with integrated power supply and waterproof connectors makes wiring simple, fast and reliable.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Luminaire light beam spread	120°
CE mark	CE mark
UL mark	-
CQC mark	CQC-mark
PSE mark	PSE mark
Operating and Electrical	
Input voltage	100 to 240 V
Input frequency	50 to 60 Hz
Mechanical and Housing	
Housing material	Aluminum extruded

Optic material	Glass	
Optical cover/lens material	Tempered glass	
Optical cover/lens shape	Flat	
Optical cover/lens finish	Clear	
Colour	Dark gray	
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-	
	proof]	
Mech. impact protection code	IK07 [2 J reinforced]	
Initial Performance (IEC Compliant)		
Init. Corr. colour temperature	2700 K	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 70% at 25°C Calculated	100000	
Lumen Maintenance 70% at 25°C Reported	60000	
Lumen Maintenance 70% at 40°C Calculated	100000	

Vaya Linear LP G2

Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	87000
Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	66000
Lumen Maintenance 80% at 40°C Reported	60000
Lumen Maintenance 90% at 25°C Calculated	41000
Lumen Maintenance 90% at 25°C Reported	41000
Lumen Maintenance 90% at 40°C Calculated	31000
Lumen Maintenance 90% at 40°C Reported	31000


Product Data	
Full product code	871869921822599
Order product name	BCP422 G2 120 2700 L610 CE CQC PSE
EAN/UPC – product	8718699218225
Order code	21822599
Numerator – quantity per pack	1
Numerator – packs per outer box	4
Material no. (12NC)	912400136134
Net weight (piece)	1.100 kg

Application Conditions

Ambient temperature range

-40 to +40 °C

Dimensional drawing



Vaya Linear LP Gen2



IP 66 K 07

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, October 15 - data subject to change