



Vaya Linear LP G2

BCP422 G2 120 2700 L610 CE CQC PSE

LED High Brightness

Vaya Linear LP is a super slim outdoor linear luminaire for low-level grazing applications, with wide 120° beam or elliptical 28° x 84° optics. Its slim form factor is ideal for space-restricted applications with limited setback or allowable install height. The robust Vaya Linear LP G2 offers a variety of color and white CCT options with either static on/off- or dynamic control options via standard DMX-512. The discreet design with integrated power supply and waterproof connectors makes wiring simple, fast and reliable.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source color	Warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GT [Tempered glass]
Luminaire light beam spread	120°
CE mark	CE mark
UL mark	-
CQC mark	CQC-mark
PSE mark	PSE mark
Operating and Electrical	
Input Voltage	100 to 240 V
Input Frequency	50 to 60 Hz
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Glass

Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Initial Performance (IEC Compliant)	
Init. Corr. Color Temperature	2700 K
Over Time Performance (IEC Compliant)	
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	100000
Lumen Maintenance 70% at 40°C Reported	60000
Lumen Maintenance 80% at 25°C Calculated	87000
Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	66000

Datasheet, 2018, December 1 data subject to change


Vaya Linear LP G2

Lumen Maintenance 80% at 40°C Reported	60000
Lumen Maintenance 90% at 25°C Calculated	41000
Lumen Maintenance 90% at 25°C Reported	41000
Lumen Maintenance 90% at 40°C Calculated	31000
Lumen Maintenance 90% at 40°C Reported	31000
Application Conditions	
Ambient temperature range	-40 to +104 °F
Product Data	
Order product name	BCP422 G2 120 2700 L610 CE CQC PSE

EAN/UPC - Product	8718699218225	
Order code	912400136134	
Local order code		
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	4	
Material Nr. (12NC)	912400136134	
Net Weight (Piece)	1.100 kg	



Dimensional drawing



Vaya Linear LP Gen2

