



iColor Accent Compact, RGBW

iColor Accent Compact, RGBW, 619.5 mm (24.4 in), Translucent Lens

iColor Accent Compact, RGBW, 619.5 mm (24.4 in), Translucent Lens

iColor Accent Compact, RGBW is a direct view linear LED luminaire ideally suited for displaying large-scale video, graphics and intricately designed effects in a host of architectural settings. iColor Accent Compact, RGBW adds a separate white LED, creating better-quality whites compared to RGB. iColor Accent Compact, RGBW accepts Ethernet input from the PDS-400 48V EO to support long control runs not subject to DMX data and addressing limitations. Two lens choices are available for iColor Accent Compact, RGBW: a clear lens which delivers the brightest output and a translucent lens which provides the widest viewing angle.

Product data

General information		Colour	Aluminum	
Light source colour	RGBW			
Optical cover/lens type	PC-UV [Polycarbonate bowl/cover UV-	Approval and application		
	resistant]	Energy Efficiency Class	G	
		Vibration standard	Complies with ANSI C136.31, 3G	
Light technical		FCC mark	FCC Class A	
On-axis intensity in candela	57	Vibration rating	Complies with ANSI C136.31, 3G	
			942288	
Mechanical and housing				
Length	610 mm	Initial performance (IEC compliant)		
		Initial LED luminaire efficacy at RGB operation 31 lm/W		

iColor Accent Compact, RGBW

Initial input power	16 W
Over time performance (IEC compliant))
Lumen Maintenance 50% at 25 °C Reported	60000
Lumen Maintenance 50% at 50 °C Reported	60000
Lumen Maintenance 70% at 25 °C Reported	60000
Lumen Maintenance 70% at 50 °C Reported	60000
Lumen Maintenance 80% at 25 °C Reported	50000
Lumen Maintenance 80% at 50 °C Reported	50000


871869921872099

Order product name	BCS425 RGBW FR ETH L610 PP19		
EAN/UPC – product	8718699218720		
Order code	101-000200-08		
SAP numerator – quantity per pack	1		
Numerator – packs per outer box	9		
SAP material	912400136257		
Net Weight (Piece)	0.960 kg		
Commercial Code	101-000200-08		
Catalogue number description	iColor Accent Compact, RGBW, 619.5		
	mm (24.4 in), Translucent Lens		


Product data

Full	proa	uct	coa	5

Dimensional drawing



BCS425 RGBW FR ETH L610 PP19



BCS425 RGBW FR ETH L610 PP19



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2023, January 10 - data subject to change