



Accent Compact, RGBW



iColor Accent Compact, RGBW, 1228.5 mm (48.4 in), Translucent Lens

iColor Accent Compact, RGBW, 1228.5 mm (48.4 in), Translucent Lens

iColor Accent Compact, RGBW is a direct view linear LED luminaire ideally suited for displaying large-scale video, graphics, and intricately designed effects in a host of architectural settings. iColor Accent Compact, RGBW adds a separate white LED, creating better-quality whites compared to RGB. iColor Accent Compact, RGBW accepts Ethernet input from the PDS-400 48V EO to support long control runs not subject to DMX data and addressing limitations. Two lens choices are available for iColor Accent Compact, RGBW: a clear lens which delivers the brightest output and a translucent lens which provides the widest viewing angle.

Product data

RGBW
Polycarbonate bowl/cover UV-resistant
57
1220 mm
Aluminum

Approval and application	
Energy Efficiency Class	G
Vibration Standard	Complies with ANSI C136.31, 3G
Corrosion Resistance	Complies with ASTM B117 standard for >
	1,500 hours
FCC mark	FCC Class A
Vibration Rating	Complies with ANSI C136.31, 3G
EPREL Registration Number	942289
Initial performance (IEC compliant)	
Initial LED luminaire efficacy at RGB	34.8 lm/W
operation	


Datasheet, 2022, July 24 data subject to change


Accent Compact, RGBW

Initial input power	28.5 W	
Over time performance (IEC compliant)		
Lumen Maintenance 50% at 25°C Reported	60000	
Lumen Maintenance 50% at 50°C Reported	60000	
Lumen Maintenance 70% at 25°C Reported	60000	
Lumen Maintenance 70% at 50°C Reported	60000	
Lumen Maintenance 80% at 25°C Reported	50000	
Lumen Maintenance 80% at 50°C Reported	50000	
Product data		
Full product code	871869921873799	

Order product name	BCS425 RGBW FR ETH L1220 PP19
EAN/UPC - Product	8718699218737
Order code	101-000200-09
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9
Material Nr. (12NC)	912400136258
Net Weight (Piece)	1.640 kg
Catalog Number	101-000200-09
Catalog Number Description	iColor Accent Compact, RGBW, 1228.5
	mm (48.4 in), Translucent Lens

Dimensional drawing





BCS425 RGBW FR ETH L1220 PP19

BCS425 RGBW FR ETH L1220 PP19



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.