PHILIPS Lighting



Vaya Flood HP 150W

BCP438 RGBW 220-240 30 CE CQC

LED High Brightness - Medium beam angle 30°

Vaya Flood HP 150W is a reliable and cost effective high output LED flood lighting solution ideal for illuminating large-scale exterior facades, bridges, and monuments. While minimizing initial investment, this Vaya Flood series provides exceptional flexibility to create eye-catching flood, wash and spot lighting effects. A choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source color	RGBW
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Flat glass
Luminaire light beam spread	30°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	-
Optic type outdoor	Medium beam angle 30º
PSE mark	No
Angle	30°
Operating and Electrical	
Input Voltage	220 to 240 V

Input Frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum die cast
Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Color	Dark gray
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Vibration Standard	Complies with ANSI C136.31


Vaya Flood HP 150W


Vibration Rating	Complian with ANEL C126 21
Vibration Rating	Complies with ANSI C136.31
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	6518 lm
Initial input power	150 W
Over Time Performance (IEC Complian	nt)
Lumen Maintenance 50% at 25°C Calculated	100000
Lumen Maintenance 50% at 25°C Reported	36000
Lumen Maintenance 50% at 40°C Calculated	100000
Lumen Maintenance 50% at 40°C Reported	36000
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	36000
Lumen Maintenance 70% at 40°C Calculated	100000
Lumen Maintenance 70% at 40°C Reported	36000

Application Conditions	
Ambient temperature range	-40 to +40 °C
Product Data	
Full product code	871869937518800
Order product name	BCP438 RGBW 220-240 30 CE CQC
EAN/UPC - Product	8718699375188
Order code	912400136893
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912400136893
Net Weight (Piece)	10.200 kg



Dimensional drawing







Vaya Flood 150W



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, May 2 - data subject to change