



## **DuaLED Recessed**

## 2DLG49L840-4-D-UNV

2x4, 4900 Nominal Delivered Lumens, 4000K, Diffuse - 102 lm/W

DuaLED was thoughtfully developed as a sustainable luminaire with a modern appearance and uncomplicated design, also offering exceptional quality and performance, for an outstanding benefit to the customer. DuaLED is a highly efficient, architecturally styled recessed LED luminaire designed with a minimalistic strategy to achieve sustainable objectives. It combines an extremely low profile with clean aesthetics and is powered by highly efficient advanced LED sources, providing the utmost in comfortable efficient lighting. Driver and integral control options ensure optimization for every application. Designed for excellent visual comfort, DuaLED is perfect for a wide variety of general applications like offices, schools, retail, or healthcare.

## Product data

| General Information           |               |
|-------------------------------|---------------|
| Lamp Source Code              | LED           |
| Color Temperature             | 4000K         |
| CRI                           | 80            |
| Photometric Distribution Type | Direct        |
| Mounting                      | Recessed      |
|                               |               |
| Operating and Electrical      |               |
| Voltages                      | 120/277/347 V |
| Luminaire Input Watts         | 48            |
|                               |               |
| Mechanical and Housing        |               |
| Fixture Size                  | 2 ft x 4 ft   |
| Shape                         | Rectangular   |
|                               |               |
|                               |               |

| Initial Performance (IEC Compliant)                |  |
|--|--|
| 4900   |  |
| 102 lm/W   |  |
|  |  |
|  |  |
| 2DLG49L840-4-D-UNV                                 |  |
| 782343786635                                       |  |
| 912400357278                                       |  |
| 4378663  |  |
| 1  |  |
| 1  |  |
| 912400357278                                       |  |
| 0.001 kg   |  |
| 2DLG49L840-4-D-UNV-DIM                             |  |
| 2x4, 4900 Nominal Delivered Lumens, 4000K, Diffuse |  |
| Spec Smart (10 Days) USA                           |  |
|  |  |

Datasheet, 2018, July 24 data subject to change

