



LytePro 16 LED Wall Sconce

LPW16, 40W, 700mA, 4000K, 120-277V, Dark gray textured paint

LPW16, 40W, 700mA, 4000K, 120-277V, Dark gray textured paint - 93 lm/W

The architecturally styled LytePro 16 LED Wall Sconce is a compact LED luminaire designed for exterior wall mounting in commercial and residential applications. It is ideal for general-purpose illumination along perimeters, entrances and garages for safety and security installations as well as accent lighting around buildings. LytePro 16 consumes only 40 watts, and achieves up to 96 LPW to provide an efficient alternative to traditional light sources.

Product data

General Information		Approval and Application	
Lamp Source Code	LED	ETL	
Colour Temperature	4000k	DLC Standard	
CRI	70	DesignLights Consortium Qualified Product - List	
Photometric Distribution Type	Type III	Initial Performance (IEC Compliant)	
Mounting	Wall	Luminaire Lumens	3400
B.U.G. Rating	B1U0G1	Efficacy	93 lm/W
	DLC QPL	Application Conditions	
Operating and Electrical		+40 °C	
Voltages	120/208/240/277 V		
Luminaire Input Watts	36		

LytePro 16 LED Wall Sconce

	-40 °C
Product Data	
Order product name	LPW16-78DGY
EAN/UPC – product	190096011308
Order code	LPW16-78DGY
Numerator – quantity per pack	1
Numerator – packs per outer box	6

Material no. (12NC)	912400531022
Net weight (piece)	0.001 kg
Commercial Code	LPW16-78DGY
Commercial Code	LPW16, 40W, 700mA, 4000K, 120-277V, Dark gray textured paint

