



## LytePro 16 LED Wall Sconce

## LPW16-78DGY

LPW16, 40W, 700mA, 4000K, 120-277V, Dark gray textured paint - 93 lm/W

The architecturally styled LytePro 16 LED Wall Sconce is a compact LED luminaire designed for exterior wall mounting in commercial and residential applications. It is ideal for general-purpose illumination along perimeters, entrances and garages for safety and security installations as well as accent lighting around buildings. LytePro 16 utilizes only 40 watts, and achieves up to 96 LPW to provide an efficient alternative to traditional light sources.

## **Product data**

General Information	
Lamp Source Code	LED
Color Temperature	4000k
CRI	70
Photometric Distribution Type	Туре III
Mounting	Wall
B.U.G. Rating	B1U0G1
Awards	DLC QPL
Operating and Electrical	
Voltages	120/208/240/277 V
Luminaire Input Watts	36
Approval and Application	
Safety Listing	ETL

DesignLights Consortium Qualified Product List DesignLights Consortium Qualified Product List		
Initial Performance (IEC Corr	npliant)	
Luminaire Lumens	3400	
Efficacy	93 lm/W	
Application Conditions		
Max Ambient Temp	+40 °C	
Min Ambient Temp	-40 °C	
Product Data		
Order product name	LPW16-78DGY	
EAN/UPC - Product	190096011308	
Order code	LPW16-78DGY	
Local order code		

## LytePro 16 LED Wall Sconce

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	912400531022
Net Weight (Piece)	0.001 kg
Commercial Code	LPW16-78DGY

Catalog Number Description	LPW16, 40W, 700mA, 4000K, 120-277V, Dark
	gray textured paint
Quick Ship	Service Smart (2 Days) USA



© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, October 11 - data subject to change