



LytePro 32 LED Wall Sconce

LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured Dark Gray

LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured Dark Gray - 98 lm/W

The Lytepro 32 Series Architectural Wall Sconce from KEENE incorporates modern styling, high performance, and energy efficient LEDs. Featuring Philips LedGine platform for future proof designs that enhance upgrades and simplify replacements. Ideal LED solution to replace 150 watt and 175 watt HID sources with up to 60 % energy savings.

Product data

General Information		Approval and Application	
Lamp Source Code	LED	ETL	
Colour Temperature	4000K	DLC Standard	
CRI	70	DesignLights Consortium Qualified Product - List	
Photometric Distribution Type	Type III	Initial Performance (IEC Compliant)	
Mounting	Wall	Luminaire Lumens	6900
B.U.G. Rating	B2U0G2	Efficacy	98 lm/W
	DLC QPL	Application Conditions	
Operating and Electrical		+40 °C	
Voltages	120/208/240/277 V	-40 °C	
Luminaire Input Watts	71		

LytePro 32 LED Wall Sconce

Product Data	
Order product name	LPW32-78DGY
EAN/UPC – product	190096011278
Order code	LPW32-78DGY
Numerator – quantity per pack	1
Numerator – packs per outer box	3
Material no. (12NC)	912400531034

Net weight (piece)	0.001 kg
Commercial Code	LPW32-78DGY
Commercial Code	LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured Dark Gray

