

LytePro 32 LED Wall Sconce

LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured Dark Gray

LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured Dark Gray - 98 lm/W

The Lytepro 32 Series Architectural Wall Sconce from KEENE incorporates modern styling, high performance, and energy efficient LEDs. Featuring Philips LedGine platform for future proof designs that enhance upgrades and simplify replacements. Ideal LED solution to replace 150 watt and 175 watt HID sources with up to 60% energy savings.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	70
Photometric Distribution Type	Type III
Mounting	Wall
B.U.G. Rating	B2U0G2
Awards	DLC QPL

Operating and Electrical	
Voltages	120/208/240/277 V
Luminaire Input Watts	71

Approval and Application	
Safety Listing	ETL
DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List

Initial Performance (IEC Compliant)	
Luminaire Lumens	6900
Efficacy	98 lm/W

Application Conditions	
Max Ambient Temp	+40 °C
Min Ambient Temp	-40 °C

LytePro 32 LED Wall Sconce

Product Data	
Order product name	LPW32-78DGY
EAN/UPC - Product	190096011278
Order code	LPW32-78DGY
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	912400531034

Net Weight (Piece)	0.001 kg
Catalog Number	LPW32-78DGY
Catalog Number Description	LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured Dark Gray

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.