



LytePro 32 LED Wall Sconce

LPW32-79BZ

LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Bronze - 98 lm/W

The Lytepro 32 Series Architectural Wall Sconce from KEENE incorporates modern styling, high performance, and energy efficient LEDs. Featuring Philips LedGine platform for future proof designs that enhance upgrades and simplify replacements. Ideal LED solution to replace 150 watt and 175 watt HID sources with up to 60% energy savings.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000k
CRI	70
Photometric Distribution Type	Type III
Mounting	Wall
B.U.G. Rating	B2U0G2
Awards	DLC QPL
Operating and Electrical	
Voltages	347 V
Luminaire Input Watts	71
Mechanical and Housing	
Shape	Oval

Approval and Application	
Safety Listing	ETL
DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List
Initial Performance (IEC Compliant)	
Luminaire Lumens	6900
Efficacy	98 lm/W
Application Conditions	
Max Ambient Temp	+40 °C
Min Ambient Temp	-40 °C
Product Data	
Order product name	LPW32-79BZ
EAN/UPC - Product	190096011421
Order code	912400531041
Local order code	.

LytePro 32 LED Wall Sconce

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912400531041
Net Weight (Piece)	0.200 kg
Commercial Code	LPW32-79BZ

Catalog Number Description	LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Bronze
Quick Ship	Service Smart (2 Days) Canada

