



LytePro 32 LED Wall Sconce

LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Bronze

LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Bronze – 98 lm/W

The Lytepro 32 Series Architectural Wall Sconce from KEENE incorporates modern styling, high performance, and energy efficient LEDs. Featuring Philips LedGine platform for future proof designs that enhance upgrades and simplify replacements. Ideal LED solution to replace 150 watt and 175 watt HID sources with up to 60% energy savings.

Product data

General Information		Mechanical and Housing	
Lamp Source Code	LED	Shape	Oval
Colour Temperature	4000k	Approval and Application	
CRI	70	Safety Listing	ETL
Photometric Distribution Type	Type III	DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List
Mounting	Wall	Initial Performance (IEC Compliant)	
B.U.G. Rating	B2U0G2	Luminaire Lumens	6900
Awards	DLC QPL	Efficacy	98 lm/W
Operating and Electrical		Application Conditions	
Voltages	347 V	Max Ambient Temp	+40 °C
Luminaire Input Watts	71		

LytePro 32 LED Wall Sconce

Min Ambient Temp	-40 °C
------------------	--------

Product Data

Order product name	LPW32-79BZ
EAN/UPC - Product	190096011421
Order code	LPW32-79BZ
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Material Nr. (12NC)	912400531041
Net Weight (Piece)	0.200 kg
Catalog Number	LPW32-79BZ
Catalog Number Description	LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Bronze

