



LytePro LED Flood Small LPF2

STK- LPF2-E-4K-FL-K-8-BZ

Stock LPF2, 4000K, Flood, Knuckle Mount, 120-277V, Textured Dark Bronze - 87 lm/W

The Philips Keene LytePro LED Small Floodlight allows precision and flexibility in a compact design. The LPF2 features state-of-the-art long-life LED technology and is ideal for landscapes, accenting signage or displays, facades, and many other lighting applications.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	80
Photometric Distribution Type	NEMA 6H x 6V
Mounting	NPT/NPS
Operating and Electrical	
Voltages	120/208/240/277 V
Luminaire Input Watts	40
Mechanical and Housing	
Material	Aluminum
Approval and Application	
Safety Listing	UL

IP Rating	IP66	
ii raang	11 00	
Initial Performance (IEC Compliant)		
Luminaire Lumens	3460	
Efficacy	87 lm/W	
Product Data		
Order product name	STK- LPF2-E-4K-FL-K-8-BZ	
EAN/UPC - Product	190096001583	
Order code	912401050214	
Local order code		
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box 4		
Material Nr. (12NC)	912401050214	
Net Weight (Piece)	0.001 kg	
Commercial Code	STKLPF2K-8	

Datasheet, 2018, July 23 data subject to change

LytePro LED Flood Small LPF2

Catalog Number Description

Stock LPF2, 4000K, Flood, Knuckle Mount, 120-277V,

Textured Dark Bronze

