



LytePro LED Flood Medium LPF3

Stock LPF3, 4000K, Flood, Slip Fitter, 120-277V, Textured Dark Bronze

Stock LPF3, 4000K, Flood, Slip Fitter, 120-277V, Textured Dark Bronze - 82 lm/W

The Keene LytePro LED Medium Floodlight allows precision and flexibility in a compact design. The LPF3 features state-of-the-art long-life LED technology and is ideal for landscapes, accenting signage or displays, facades, and many other lighting applications.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	80
Photometric Distribution Type	NEMA 6H x 6V
Mounting	NPT/NPS
Operating and Electrical	
Voltages	120/208/240/277 V
Luminaire Input Watts	85
Mechanical and Housing	
Material	Aluminum

Approval and Application		
Safety Listing	UL	
IP Rating	IP66	
Initial Performance (IEC Compliant)		
Luminaire Lumens	7012	
Efficacy	82 lm/W	
Product Data		
Order product name	STK- LPF3-C-4K-FL-S-8-BZ	
EAN/UPC - Product	190096001590	
Order code	STKLPF3S-8	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box 2		
Material Nr. (12NC)	912401050215	

Datasheet, 2019, May 8 data subject to change

LytePro LED Flood Medium LPF3

Net Weight (Piece)	0.001 kg
Catalog Number	STKLPF3S-8
Catalog Number Description	Stock LPF3, 4000K, Flood, Slip Fitter, 120-277V,
	Textured Dark Bronze



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.