



FBX LED High Bay

FBX20LL40-UNV

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Acrylic Lens - 124 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

General Information		
Color Temperature	4000K	
CRI	80	
Photometric Distribution Type	Direct	
Mounting	Suspended	
Operating and Electrical		
Voltages	120/208/240/277/347/480/UNIV V	
Luminaire Input Watts	142	
Mechanical and Housing		
Fixture Size	24 in	
Initial Performance (IEC Compliant)		
Luminaire Lumens	20000	
Efficacy	124 lm/W	

Product Data	
Order product name	FBX20LL40-UNV
EAN/UPC - Product	782343501504
Order code	912401266801
Local order code	4350150
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401266801
Net Weight (Piece)	0.001 kg
Commercial Code	FBX20LL40-UNV-LFA
Catalog Number Description	20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General
	Distribution, Frosted Acrylic Lens

Datasheet, 2018, October 5 data subject to change