



## LSW Wall LED

## LS4R40A40U

Ceiling Or Wall Mounted Fluorescent, 6" Width, 3 7/8" Deep, 4000 nominal lumens, 4000K color temperature - 89 lm/W

LSW Lens Wrap Ceiling/Wall Mounted - Specification Grade For ceiling or wall (vertically or horizontally) mounted applications. Only 3 7/8" deep, meets Americans with Disabilities Act (wall mounted). Low brightness .125 thick linear prismatic virgin acrylic refractor. Invisible spring steel latches align refractor to housing. 20 gauge cold rolled steel post painted baked white enamel end caps. For over mirror, over bed, corridor, stairwell and bulletin board applications.

## **Product data**

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Wall Surface
Operating and Electrical	
Voltages	120/277/347/UNIV V
Luminaire Input Watts	45
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	
Luminaire Lumens	4000
Efficacy	89 lm/W

Product Data	
Order product name	LS4R40A40U
EAN/UPC - Product	781370294946
Order code	912401267051
Local order code	7029494
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401267051
Net Weight (Piece)	0.001 kg
Commercial Code	LS4R40A40UDZT
Catalog Number Description	Ceiling Or Wall Mounted Fluorescent, 6" Width, 3 7/8" Deep,
	4000 nominal lumens, 4000K color temperature
Quick Ship	-

Datasheet, 2018, July 24 data subject to change

## **LSW Wall LED**

