



APX LED High Bay

APX16LL40-UNV

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution - 128 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	123
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	
Luminaire Lumens	16000
Efficacy	128 lm/W

Product Data	
Order product name	APX16LL40-UNV
EAN/UPC - Product	784197052867
Order code	912401272275
Local order code	9705286
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401272275
Net Weight (Piece)	0.001 kg
Commercial Code	APX16LL40-UNV-N
Catalog Number Description	16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow
	Distribution
Quick Ship	-

Datasheet, 2018, August 7 data subject to change

APX LED High Bay

