



APX LED High Bay

APX16LL40-UNV

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium
Distribution - 129 lm/W

The APX LED High Bay provides durability and high performance for your customer’s demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	123
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	
Luminaire Lumens	16000
Efficacy	129 lm/W

Product Data	
Order product name	APX16LL40-UNV
EAN/UPC - Product	784197056384
Order code	912401272283
Local order code	9705638
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401272283
Net Weight (Piece)	0.001 kg
Commercial Code	APX16LL40-UNV-M
Catalog Number Description	16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution
Quick Ship	-

APX LED High Bay

