



APX LED High Bay

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution – 128 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	123
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	
Luminaire Lumens	16000

Efficacy	128 lm/W
Product Data	
Order product name	APX16LL40-UNV
EAN/UPC - Product	784197056315
Order code	APX16LL40-UNV-A
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401272284
Net Weight (Piece)	0.001 kg
Net Weight (Piece) Catalog Number	0.001 kg APX16LL40-UNV-A

Datasheet, 2019, May 6 data subject to change