



# APX LED High Bay

## 8,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution - 129 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

### Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended

  

Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	76

  

Mechanical and Housing	
Fixture Size	48 in

  

Initial Performance (IEC Compliant)	
Luminaire Lumens	8000

  

Efficacy	129 lm/W
----------	----------

  

Product Data	
Order product name	APX08LL40-UNV
EAN/UPC - Product	784197056353
Order code	APX08LL40-UNV
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401272289
Net Weight (Piece)	0.001 kg
Catalog Number	APX08LL40-UNV
Catalog Number Description	8,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution